



Contour-Ty® CBR1.5I-M30 Cable Tie

CBR1.5I-M30

Panduit Contour-Ty® Cable Ties are designed to provide consistent strength in high-vibration environments. Plus, with a low-profile head and parallel entry design, the tip enters easy and stays snug and snag-free. And with Heat Stabilized Nylon 6.6 material it's ideal for temperatures up to 239 degrees. Intermediate cross section, 5.9in, Tensile Strength: 178, Black, 1000pc.

Specifications

Material Description	Nylon 6.6 (Heat-Resistant)
Product Type	Cable Tie
Sub Brand	Contour-Ty®
Color	Black
Environment	Indoor
Material	Nylon 6.6
Resistance Properties	Heat-Resistant
Overall Length (In.)	5.8
Overall Length (mm)	147.3
Body Width (In.)	0.14
Body Width (mm)	3.6
Body Thickness (In.)	0.042
Body Thickness (mm)	1.1
Maximum Bundle Diameter (In.)	1.5
Maximum Bundle Diameter (mm)	38.1
Minimum Bundle Diameter (In.)	0.07
Minimum Bundle Diameter (mm)	1.8
Minimum Loop Tensile Strength (N)	178
Minimum Loop Tensile Strength (lb)	40
Maximum Operating Temperature (°C)	115
Maximum Operating Temperature (°F)	239
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	SAE-AS23190A, SAE-AS33671, RoHS Compliant
Military Cross Reference Number	MS3367-33-11
For Use With	GTS-E, GS2B, PTS, PPTS, STS2