



Contour-Ty® CBR1M-M30 Contour Cable Tie, Black, High Heat PA6.6, 4.1"L, 18lb

CBR1M-M30

Panduit CBR1M-M30 Contour-Ty® Cable Ties are designed to provide consistent strength in high-vibration environments. A low-profile head and parallel entry design, the curved tip enters easily and stays snug and snag-free. Miniature cross section, 4.1” (104mm) length. Appropriate for Indoor use. Made of Heat Stabilized Nylon 6.6 for high applications, are black in color and come in packages of 1000.

Specifications

Material Description	Nylon 6.6 (Heat-Resistant)
Product Type	Cable Tie
Sub Brand	Contour-Ty®
Color	Black
Environment	Indoor
Material	Nylon 6.6
Material Properties	Heat-Stabilized
Resistance Properties	Heat-Resistant
Overall Length (In.)	4.1
Overall Length (mm)	104
Body Width (In.)	0.098
Body Width (mm)	2.5
Body Thickness (In.)	0.038
Body Thickness (mm)	1
Maximum Bundle Diameter (In.)	1
Maximum Bundle Diameter (mm)	25.4
Minimum Bundle Diameter (In.)	0.07
Minimum Bundle Diameter (mm)	1.8
Minimum Loop Tensile Strength (N)	80
Minimum Loop Tensile Strength (lb)	18
Maximum Operating Temperature (°C)	115
Maximum Operating Temperature (°F)	239
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4