

7 6 5 4 3 2 1

REV B	SRK-BS-FL-ST-***	REVISIONS			
		SYM	DESCRIPTION	DATE	APPROVED
		A	NEW RELEASE PER E.O. P20387	12-1-09	R.D.R.
		B	REVISED AND REDRAWN PER E.O. P20600	8-31-10	RDR

SRK - BS - FL - ST - 001

SERIES PREFIX

BACKSHELL BS




SIZE FL FULL

VERSION OF CORRUGATED CONDUIT
001 NW22
002 NW26


ST STRAIGHT

CONVOLUTE REQUIREMENTS:
RATED 125°C
NW22
OUTER Ø=25.40 [1.000]
INNER Ø=21.30 [.839]
PITCH=3.10 [.122]
NW26
OUTER Ø=31.20 [1.228]
INNER Ø=25.80 [1.016]
PITCH=3.40 [.134]

VERSION OF CONDUIT	X mm [inches]	Y mm [inches]	Z mm [inches]
001	33.00 [1.299]	21.50 [.846]	3.10 [.122]
002	32.00 [1.260]	26.40 [1.039]	3.50 [.138]



SECTION A-A



- 4. MATERIAL: PLASTIC; COLOR: BLACK.
- 3. THIS PART SNAPS ONTO SRK02-FL*-*-* AND SRK06-FL*-*-*
* = KEYS; *** = SEE 37322C-00013-01 FOR ARRANGEMENTS.
- 2. DIMENSIONAL TOLERANCE: ±.64 [.025].
- 1. ALL DIMENSIONS ARE IN MILLIMETERS [INCHES].

NOTES: UNLESS OTHERWISE SPECIFIED

SIGNATURE & DATE		BACKSHELL STRAIGHT FULL SIZE (FL) SRK SERIES	EP 201 MATL. CODE 89 3850 INDUSTRIAL AVE. HEMET, CA 92545 DEUTSCH INDUSTRIAL
DR	JAIME APOSTOL 30AUG2010		
CHK	D. Meyer 8/31/10		
PE	D. Meyer 8/31/10		
APPD	R. P. 8/31/10	ENVELOPE	C SRK-BS-FL-ST-***
SCALE	NONE		
WT	32.20 g		
DWG SIZE	11139		SHEET 1 OF 1

7 6 5 4 3 2 1