







REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	26MAY2021	V.T	Z.Z
	A1	ECN-23-231081	14AUG2023	V.T	Z.Z



SECTION A-A



CODING 1
PN:2389578-1

CODING 2
PN:2389578-2

NOTES:

1.GENERAL TOLERANCE:±0.3

2.APPLICABLE WIRE SIZE

INSULATION DIA(MM)	WIRE EXAMPLE	INSERTABLE POSITION
Ø2.0~Ø2.2	AVSS 1.25	1,9,10,17,18,25,26,34
Ø1.6~Ø1.9	AVSS 0.5~0.85	ALL POSITION

3.PRINTING MANUFACTURED DATE CONTROL No.(LOT No.)



4.PART NUMBER OF CAP ASSEMBLY TO BE MATED:SEE TABLE-1

2389578-2	1473427-1 (60Pos.)
	2-1447232-4 (34Pos.)
	1437288-2 (34Pos.)
	2-1437285-6 (34Pos.)
	6473427-1 (60Pos.)
	2-6447232-4 (34Pos.)
	6437288-2 (34Pos.)
2389578-1	2-6437285-6 (34Pos.)
	1437288-3 (60Pos.)
	1437288-5 (60Pos.)
	2-1447232-3 (34Pos.)
	1437288-1 (34Pos.)
	2-1437285-5 (34Pos.)
	6437288-3 (60Pos.)
PART NUMBER	6437288-5 (60Pos.)
	2-6447232-3 (34Pos.)
	6437288-1 (34Pos.)
	2-6437285-5 (34Pos.)
MATING CAP ASSEMBLY	





TABLE-1

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN V.TANG	25MAY2021	TE Connectivity		
DIMENSIONS: mm		CHK C.WAN	26MAY2021			
TOLERANCES UNLESS OTHERWISE SPECIFIED: 		APVD Z.ZHOU	26MAY2021			
0 PLC ± 1 PLC ± 2 PLC ± 3 PLC ± 4 PLC ± ANGLES ± FINISH -		PRODUCT SPEC 108-78140 APPLICATION SPEC 114-160220 WEIGHT -				
MATERIAL -		CUSTOMER DRAWING		NAME SUPER SEAL CONNECTOR PLUG HOUSING 34Pos. ASSEMBLY (SINGLE)	SIZE A2	CAGE CODE 00779
				DRAWING NO C=2389578	RESTRICTED TO -	REV A1
				SCALE 2:1	SHEET 1 OF 2	

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-



SECTION A-A



CODING 1
PN:2389578-3

CODING 2
PN:2389578-4

NOTES:

- 1.GENERAL TOLERANCE:±0.3
- 2.APPLICABLE WIRE SIZE

INSULATION DIA(MM)	WIRE EXAMPLE	INSERTABLE POSITION	CONTACT
Ø1.2~Ø1.3	0.35	ALL POSITION	3-1447221-5

3. PRINTING MANUFACTURED DATE CONTROL No.(LOT No.)

4.PART NUMBER OF CAP ASSEMBLY TO BE MATED:SEE TABLE-1

2389578-4	1-2388688-4 (34Pos.)
2389578-3	1-2388688-3 (34Pos.)
PART NUMBER	MATING CAP ASSEMBLY

TABLE-1

1	1	RED BROWN	SILICON RUBBER	SEAL RING	6
1	1	GREY	SILICON RUBBER	FAMILY SEAL	5
1	1	BLACK	PBT-GF15	LOCKING&BACKPLATE	4
1	1	BLACK	PBT-GF15	INITIAL LOCK	3
1	1	WHITE	PBT/PET GF30	FINAL LOCK	2
1		BLACK	PBT-GF30	SOCKET INSULATOR, CODE 2	1
	1	BLACK	PBT-GF30	SOCKET INSULATOR, CODE 1	
QTY. REQUEST PER ASSY		COLOR	MATERIAL	DESCRIPTION	ITEM NO
24.1	24.1	WEIGHT OF EACH ASSY NO. (g)			
A	A	REVISION OF EACH ASSY NO.			
2389578-4	2389578-3	TE ASSEMBLY PN			

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN V.TANG	25MAY2021	 TE Connectivity			
		CHK C.WAN	26MAY2021				
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME SUPER SEAL CONNECTOR PLUG HOUSING 34Pos. ASSEMBLY (DOUBLE)			
		APVD Z.ZHOU					
		PRODUCT SPEC		SIZE			
		-		CAGE CODE			
		APPLICATION SPEC		DRAWING NO			
		-		RESTRICTED TO			
		WEIGHT		A2		00779	
		-		C=2389578		-	
MATERIAL		FINISH		CUSTOMER DRAWING			
-		-		SCALE		2:1	
-		-		SHEET		2 OF 2	
				REV		A1	